

MINI STAMPER

Model 12

- **COMPACT!**
- **CLEAN ROOM READY!**
- **EASILY TRANSPORTED!**

The Mini Stamper is designed specifically for hot stamping small medical parts in a clean room. The Mini Stamper should be considered for printing on luer "Y" and "T" fittings when lot code, product code, and date codes are required.

Features

- Small footprint: 38"h x 24"w x 12"d
- Clean room ready
- Pneumatic system is designed to run dry
- Anodized black aluminum surfaces
- Stainless steel hardware
- Light weight: 60 lbs.
- MicroProcessor Controlled:
 - Printing Time
 - Foil Pull Delay
 - Foil Pull Time
- Digital temperature controller with solid state relay
Range: 200 to 600 degrees F
- Light Touch Palm Buttons
- Micrometer depth stop
- Dovetail die holder

Specifications

- Power input: 120 VAC 5 amp 50/60 Hz.
(Optional 220 VAC 2.5 amp 50/60 Hz.)
- Air supply: 100 psig at 0.5 cfm, clean dry air
- Dimensions: 38"h x 24"w x 12"d
- Weight: 60 lbs.
- Printing pressure: 50 to 500 lbs.
- Printing time: 0.001 to 9.999 digital control
- Heater head size: 2" x 4" 350 watt



Options

- Side to Side Slide
- Light Curtain System
- Numbering heads
- Heater head, 3" x 6" 600 watt



1313 East Borchard Ave. Santa Ana, Ca 92705
Phone (714) 547-0194 Fax (714) 542-2728

"SERVING THE PLASTICS INDUSTRY SINCE 1979 WITH
SYSTEMS AND SERVICES FOR SECONDARY FINISHING"

www.afmeng.com cirwin@afmeng.com